



Concept-Smart K

Clorador salino compacto en caja IP65 con display digital y producciones de 10 a 35 gramos destinados para piscinas privadas

- Menor consumo eléctrico
- Menor peso
- Más protección al grado de estanqueidad (IP65)
- Menor temperatura de trabajo
- Más compacto, fácilmente adaptable a cualquier caseta de instalación
- Mayor rendimiento en la cloración salina al trabajar con fuentes conmutadas de última generación
- Mayor durabilidad de la célula de electrólisis
- Control por microprocesador interno, que nos determina las horas de funcionamiento del equipo
- Display digital de control, fácil e intuitivo de usar

Compact salt water chlorinator in IP65 box with digital display and productions from 10 to 35 grams for private pools

- Lower electrical consumption
- Lower weight
- (IP65) waterproof index
- Lower operating temperature
- More compact, easily adaptable to any installation
- Switch mode power supply improves importantly the unit performance
- Longer durability of the electrolysis cell
- Internal microprocessor control, that determines the device operating hours
- Digital display, easy and intuitive use control

	C10-SK	C15-SK	C20-SK	C25-SK	C35-SK	
Tensión de alimentación	230Vac – 50Hz / 60Hz					Power supply
Corriente máxima de la célula	10A	15A	20A	25A	35A	Max cell current
Potencia máxima	75W	112.5W	150W	187.5W	263W	Max power
Tensión máxima de la célula	7.5Vcc					Max cell voltage
Sal necesaria *	> 2gr/l					Salt required *
Selección de idioma	●	●	●	●	●	Language selection
Regulación de cloro manual	●	●	●	●	●	Manual regulation of chlorine
Regulación de cloro automático	●	●	●	●	●	Automatic regulation of chlorine
Indicación de lectura redox	●	●	●	●	●	Indicator of ORP values
Indicación de lectura pH	●	●	●	●	●	Indicator of pH values
Indicación falta de sal	●	●	●	●	●	Automatic indicator of lack of salt
Indicación exceso de sal	●	●	●	●	●	Automatic indicator of salt excess
Indicación T° del agua	●	●	●	●	●	Indicator of water T°
Autolimpiable	●	●	●	●	●	Self-cleaning

DESCONEXIONES AUTOMÁTICAS

	C10-SK	C15-SK	C20-SK	C25-SK	C35-SK	
Por falta de flujo de agua	●	●	●	●	●	Caused by lack of water flow
Por acumulación de gas en la célula	●	●	●	●	●	Caused by gas accumulation in the cell
Por sobrecarga	●	●	●	●	●	Caused by overload
Por cortocircuito	●	●	●	●	●	Caused by short circuit
Por sobre temperatura	●	●	●	●	●	Caused by over temperature

AUTOMATIC STOPPINGS

OPCIONES

	C10-SK	C15-SK	C20-SK	C25-SK	C35-SK	
Kit sonda Smart/1	●	●	●	●	●	Smart/1 probe Kit
Kit pH	●	●	●	●	●	Kit pH
Kit sonda temperatura	●	●	●	●	●	Temperature probe Kit
Kit sonda Amperométrica	●	●	●	●	●	Amperometric probe Kit

OPTIONS

(*) Los equipos empiezan a trabajar a partir de 2 gramos / litro pudiendo llegar a trabajar con valores de 35 gramos / litro (agua de mar) con una modificación del software

(*) Working concentration from 2 to 35 grams / liter (sea water) with software modification

MEDIDA

C10-SK	C15-SK	C20-SK	C25-SK	C35-SK
280 x 250 x 135mm 4Kg				

OVERALL DIMENSIONS